


GRANDE

Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing intervals [mm]	Connections distance from the wall [mm]	Brackets spacing intervals [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power (75/65/20 °C) [W]	Power (75/65/24 °C) [W]	Power (55/45/24 °C) [W]	Electric heater maximal power [W]
W	H	D	C	B	A							
600	600	81	50	58	400	1,42	19,4	11,1	403	363	177	-
600	486	81	50	58	400	1,17	16,5	9,3	331	298	146	-
1000	600	81	50	58	800	2,29	29,4	17,5	671	604	295	-
1000	486	81	50	58	800	1,88	24,6	14,5	552	497	244	-
1400	600	81	50	58	1200	3,16	39,4	23,9	939	846	413	-
1400	486	81	50	58	1200	2,59	32,7	19,7	773	696	342	-
1800	600	81	50	58	1600	4,03	49,4	30,3	1208	1088	531	-
1800	486	81	50	58	1600	3,29	40,8	24,9	994	895	439	-
2200	600	81	50	58	2000	4,90	59,4	36,6	1476	1329	648	-
2200	486	81	50	58	2000	4,00	48,9	30,1	1214	1094	537	-



Vertical manifolds (untypical);
2 mm thick tube

Finishing and warranty:

- phosphatizing + electrophoresis + polyester-epoxy lacquer;
10 year warranty;

Mounting brackets:

Galvanized snap fastener mounting brackets are included

Heater:

-

Working pressure:

10 bars

Maximal temperature:

95 °C

Connections:



inner threads G 1/2
air-vent plug G1/8 hidden behind

Remarks:

- Location of connections and the feed pipe:
on the left side of the radiator
- Connections to the right side available upon request (in this case the feed pipe
is on the right side, whereas the return pipe is on the left)

