



Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power (75/65/20°C) [W]	Power (75/65/24°C) [W]	Power (55/45/24°C) [W]	Electric heater maximum power [W]
W	H	D	C	B								
450	871	60-65	420	45-50	420	0,52	9,8	4,6	260	234	115	-
450	1195	60-65	420	45-50	420	0,70	13,1	6,2	351	317	155	300
450	1519	60-65	420	45-50	420	0,89	16,3	7,9	443	399	196	300
600	1195	60-65	570	45-50	570	0,88	16,3	6,7	441	398	195	300
600	1519	60-65	570	45-50	570	1,11	20,4	8,5	555	500	245	300

Horizontal profiles:



Vertical manifolds:



Finishing and warranty: Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;

Mounting brackets: brackets in the colour of the radiator are included

Working pressure: 8 bars

Maximum temperature: 95°C

Connections:



- inner threads G 1/2
- air-vent plug G 1/2 screwed in the upper hole of the collector, included

